

Waterproof SIP Column Speaker
Features

- ▶ This series of network SIP column speakers integrate with network audio decoding, digital amplifier
- ▶ With a standard RJ45 network interface and supports online firmware upgrade from long distance
- ▶ Empowered by high-speed dual-core (ARM + DSP) chip of industrial grade, startup in less than 1s
- ▶ IP65 water-proof column speaker available at 30W, 60W and 90W
- ▶ Support MP3, WMA, WAV and more decoding



Model with suffix "POE" means powered over Ethernet

DC24V Power Input

RJ45 Port

Alarm Input

Model	IPLM-630S/IPLM-630SPOE	IPLM-660S/IPLM-660SPOE	IPLM-690S
Rated Power	30W@8ohm	60W@4ohm	90W@2.7ohm
SPL (1M/1W)	90±2dB	91±2dB	92±2dB
Speakers	3" x1, 5" x1	3" x1, 5" x2	3" x1, 5" x3
Network Protocol	SIP	SIP	SIP
Network Interface	10/100Base-TX, RJ45	10/100Base-TX, RJ45	10/100Base-TX, RJ45
Audio Decoding	MP3, WMA, WAV	MP3, WMA, WAV	MP3, WMA, WAV
Frequency Response	90Hz-18KHz	90Hz-18KHz	90Hz-18KHz
Material	Aluminum	Aluminum	Aluminum
IP Rating	IP65	IP65	IP65
Power Supply	24V DC / 24V DC or PoE	24V DC / 24V DC or PoE	24V DC
Product Size	428x170x148mm	577x170x148mm	733x170x148mm
Net Weight	3.5kg	5.0kg	5.9kg